

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)October 25, 1960
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. Brownson-Argo Well No. 1 in B
(Company or Operator) Lessee (Unit)
NW 1/4 NE 1/4 of Sec. 9, T. 22S, R. 37E, NMPM, Blinabry & Tubb Pool
(40-acre Subdivision) Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 6569'

PSTD: 6567'

Perfs: Blinabry: 5505-5523, 5536-5566, 5706-5724, 5748-5764, 5778-5788, 5973-5981, 5987-5996, 6015-6020, Tubb: 6133-6180

CIBP @ 5810' & 6045'

Packer @ 6108.

5" Csg, 15# XL, Set @ 6569', Top cement @ 2700'.

Propose to kill well w/ls crude, spot 100 gals "BJ" Fern Gel in perfs 5706-5788, spot 100 gals "BJ" Fern Gel in perfs 5505-5566, drill (by reverse circ) & push CIBP @ 5810 to 6030', pull bit, run tbg w/retrievable cementer and 2 jts tail pipe to 5900', swab to test perfs 5973-5981, 5987-5996, 6015-6020, & if no test squeeze perfs 5973-5981, 5987-5996, 6015-6020 w/75 sks of Low Fluid Loss cement to 1000 psi w/hesitation squeeze method, WOC 12 hrs. Drill out cement, CIBP @ 6045 & Baker Model "D" Pkr @ 6108' down to 6300'. Run tbg w/Otis Type "J" Seating Nipple below pkr and Otis Type "A" Sliding side door above pkr set @ 6110' w/2 jts tail pipe. Swab both sides of well to complete.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Socony Mobil Oil Company, Inc.
Company or Operator

By.....

Position.....
Send Communications regarding well to:Name Socony Mobil Oil Company, Inc.Address Box 2406, Hobbs, New Mexico