

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	X	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Hobbs, New Mexico
 (Place)

January 10, 1962
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. **Brunson Argo** Well No. **11** in **A**
 (Company or Operator) (Unit)
NE $\frac{1}{4}$ **NE** $\frac{1}{4}$ of Sec. **9**, T. **22S**, R. **37E**, NMPM., **Brunson** Pool
 (40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 7645
 Csg: 13 3/8" @ 1120 w/800 sx., 8 5/8" @ 3797 w/800 sx., 5 1/2" @ 7644 w/750 sx.
 Perfs: 7615-7637

Propose to pull 2 3/8" tbg. Run GR-N Isotron log surface to TD. Run GR-N Isotron collar log surface to TD. Set bridge plug @ 7550' & dump cement on top of bridge plug. Perforate 2 holes @ 5300' & attempt to circ. around csg. If circ. cannot be established run DM retainer on 2" tbg. & block squeeze. Then perf. 2 holes @ 5050', circ. around csg., cement csg. by displacement method. Drill out cement to 5300'. Perforate Paddock zone at interval indicated by logs. Run tbg. & pkr. to 5050'. Swab test. If water free, acidize w/500 gals. 15% NE Acid followed by 5000 gals. of acid kerosene emulsion (90% Acid + 10% Kerosene) and sufficient ball sealers to seal 90% of the holes. Test and attempt completion in the Paddock formation.

Approved....., 19.....
 Except as follows:

Socony Mobil Oil Company, Inc.
 Company or Operator

By J. McDaniel

Position **Group Supervisor**

Send Communications regarding well to:

Approved
 OIL CONSERVATION COMMISSION

By.....

Name **Socony Mobil Oil Company, Inc.**

Title.....

Address **Box 2406, Hobbs, New Mexico**