

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed John H. O'Neil
Title Engineer

The summary on this page is for the condition of the well at above date.

Commenced drilling May 21, 1953 Finished drilling June 16, 1953

(Denote gas by G)

No. 1, from **5080** to **5180 oil** ----- No. 4, from **6464** to **6510 oil** -----
 No. 2, from ----- to ----- No. 5, from **6345** to **6454 gas** -----
 No. 3, from ----- to ----- No. 6, from ----- to -----

No. 1, from 80 to 175 No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
10-3/4	32.75	8	Natl	165	Box Pattern				Surface
7-5/8	26.4	8		2780	Float				Intermediate
5-1/2	15.5	8		6465	Float				Prod.

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
10-3/4	165	180	Perkins Plug	8.6	
7-5/8	2780	800	"	9.4	
5-1/2	6465	300	"	9.0	

Heaving plug—Material _____ Length _____ Depth set _____
Adapters—Material _____ Size _____

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

Rotary tools were used from 0 feet to 6510 TD feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

July 6, 1933	Put to producing June 23, 1953
The production for the first 24 hours was 36 barrels of fluid of which 100 % was oil;	
emulsion; % water; and % sediment.	Gravity, °Bé.
If gas well, cu. ft. per 24 hours	Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.	

C. J. Sanders	Driller	S. L. Gibbs	Driller
C. G. Gibbs	Driller		Driller

FROM—	TO—	TOTAL FEET	FORMATION
0	80		Caliche and Red Beds
80	175		Water Sand
175	1124		Red Beds
1124	1207		Anhydrite
1207	2400		Salt and Anhydrite
2400	2605		Anhydrite and Red Beds
2605	2710		Sand and Anhydrite
2710	3413		Dolomite and Anhydrite
3413	3475		Sand
3475	3570		Dolomite and Sand
3570	3880		Sandy Dolomite
3880	5040		Dolomite
5040	5080		Sand and Dolomite
5080	5327		Dolomite
5327	5473		Sandy Dolomite
5473	6000		Dolomite
6000	6130		Sand and Sandy Dolomite
6130	6406		Dolomite
6406	6510		Dolomite with Limestone stringers

