Form 9-331a (May 1939)

(SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<u>X</u>	SUBSEQUENT REPORT OF WATER SHUT-OFF
		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
		SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR
		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

			, 19			
Well No. <b>2-3-9</b> is lo	cated in the second s	from N line a	nd <u>a10.</u> ft. fro	$\mathbf{m} \left\{ \begin{matrix} \mathbf{E} \mathbf{x} \\ \mathbf{W} \end{matrix} \right\}$ line of so	ec9	
NY is of NY is		373	<b>封</b> 道② <b>其</b>			
(% Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)			
P	Lea	•	New	Kex160		
(Field)	(Cor	inty or Subdivision)		(State or Territory)		

The elevation of the derrick floor above sea level is \_\_\_\_\_ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to drill this well to a total depth of 8200 feet to complete in Ellenberger pay found in Ferrose Federal Well Ne 1-3-9 Tex28 X-37E at a depth of 7946'. Is proposed to use the fellowing casing pattern. Not 13 3/6" 487 at 850' and circulate cement to the surface. Set 9 5/8" 327 at 8800 to 8000' and cement back to 13 3/8". Not 32" 17% at approximately 8100' or through pay section and cement with 350 max. It is proposed to drill this well with rotary equipment.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Rewas Drilling Company

Address Fort Borth, Texas

Title Asst Goologi

\_\_\_\_\_

U. S. GOVERNMENT PRINTING OFFICE 16 - 8437