

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

12 September 1948

Monument, New Mexico

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the  
Amerada Petroleum Corporation A. B. Baker Well No. 4 in the

SE<sup>1</sup> SE<sup>1</sup> of Sec. 10, T. 22S, R. 37E, N. M. P. M.,  
Brinkard Field, Lea County.

The dates of this work were as follows: September 9-12, 1948

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on September 9, 1948  
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6475' Total Depth, Lime. Ran temperature survey and found top of cement at 2989', 94.2% of ~~calc~~ calculated fill. Nipped up 5 1/2" casing, went in hole with 4-3/4" bit and drilled out cement 6383' - 6471'. Tested casing with 1000# for 30 minutes before and after drilling cement and OK. Strapped out and 6471' = 6473'. Perforated 5 1/2" casing 6432' - 6473', 164 shots. Ran Lane Wells Gamma and Neutron Ray Survey before perforating. Ran 209 jts. of 2-3/8" OD, EUE, 4.7#, J-55, R-2, 8-RT, SS Tbg. New and Guiberson Hookwall Packer with 1-10' handling sub and 1-3' perf. sub bull plugged on bottom of tbg. Displaced mud with 180 bbls. oil and 30 bbls. went into formation. Left packer swinging.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Farm Boss  
Name Company Title

Subscribed and sworn before me this  
12th. day of September 19 48

I hereby swear or affirm that the information given above is true and correct.

Name Don Taylor  
Position Ast. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED 10 1948

Date \_\_\_\_\_

Don Taylor  
Name  
Title

