

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Clean out &amp; Frac</b>	<b>X</b>	NOTICE OF INTENTION (OTHER) <b>Rpr. Csg. Leak</b>	<b>X</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(Place)

June 6, 1955  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Eaves

Gulf Oil Corporation  
(Company or Operator)

Well No. 1 in A  
(Unit)

NE  $\frac{1}{4}$  NE  $\frac{1}{4}$  of Sec. 10, T. 22-S, R. 37-E, NMPM, Petrose Skelly Pool

Lea County.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**Propose to clean out with sand pump, if warranted. Treat open hole formation from 3549-3700' with 8000 gallons gelled lease crude oil, 1# sand per gallon.**

**If oil production has increased, will repair casing leak as follows:**

1. Set magnesium bridge plug in base of 5-1/2" casing with 1 sack cement on top.
2. Run HEC tool and locate leak.
3. If no leaks are found below 350', cement thru leak by plug method. Attempt to circulate cement out 5-1/2" - 9-5/8" annulus (leak has been established between depths of 291-321').
4. WOC 72 hours. Drill out cement and clean out to bridge plug. Pressure test 5-1/2" casing. If OK drill out bridge plug and return well to production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Gulf Oil Corporation  
Company or Operator

By [Signature]  
Position Area Supt. of Prod.

Send Communications regarding well to:

Gulf Oil Corporation

Box 2167, Hobbs, N. M.