

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

December 20, 1946

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Place

Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

Baker "B"

Well No. 6

in SW SW

Company or Operator

Lease

of Sec. 10, T. 22S, R. 37E, N. M., P. M., Penrose-Skelly, Lea County.

N

The well is 510 feet (N) of the South line and 510 feet (E.) (W) of the West line of Section 10-22S-37E, Lea County.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is

Skelly Oil Company

Address

Tulsa, Oklahoma

AREA 640 ACRES

LOCATE WELL CORRECTLY

from top to total

We propose to drill well with drilling equipment as follows: Rotary tools
depth - approximately 7800'.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17"	13-3/8"	45#	New	200'	Cemented	200 sacks
11-1/4"	8-5/8"	36#	New	2800'	Cemented	1300 sacks
6-1/2"	5-1/2"	17#	New	7800'	Cemented	750 sacks

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 7600 feet.

Additional information: In cementing the string of surface pipe cement will be circulated back to bottom of cellar. Halliburton Process will be used on all cementing jobs.

Approved DEC 27 1946, 19

except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

District Superintendent

Send communications regarding well to

Name

Skelly Oil Company

Address

Drawer D, Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

