

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

March 27, 1948

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL CO.

Baker "B"


Well No. 11 in SW/4 SE/4

Company or Operator

Lease

of Sec. 10, T. 22S, R. 37E, N. M. P. M., Drinkard Field, Lea County.

N



AREA 36 ACRES

The well is 880 feet (N.) of the Southline and 1760 feet

(E.) (W.) of the East line of Sec. 10

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is A. B. Baker

Address Eunice, New Mexico

If government land the permittee is

Address

The lessee is SKELLY OIL CO.

Address Tulsa, Okla.

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

~~Rotary tools from top to total depth.~~

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17 1/2"	13-3/8"	40.5#	New	160'	Cemented	150
11"	9-5/8"	36#	New	2815'	Cemented	1000
8 1/2"	7"	23#	New	6600'	Cemented	500

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 6500 feet.

Additional information: Halliburton Process shall be used to cement all casing strings, and sufficient time shall be allowed for cement to thoroughly set before drilling plugs.

Approved MAR 27 1948, 19

except as follows:

Sincerely yours,

SKELLY OIL CO.

Company or Operator

By

District Supt.

Position

Send communications regarding well to

Name Skelly Oil Co.

Address Hobbs, N. M.

OIL CONSERVATION COMMISSION,

By Roy W. H. H. H.

Title OIL & GAS INSPECTOR

•

Condition	Control (%)	MCI (%)	AD (%)
A	~95	~75	~55
B	~92	~80	~60
C	~90	~75	~50
D	~95	~85	~65

•

133

11

11

173