

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

AUG 26 1948

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

August 25, 1948

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Company

Baker "B"

Well No. 12

in NE 1/4 SW 1/4

Company or Operator

Lease

of Sec. 10, T. 22S, R. 37E, N. M., P. M., Drinkard Field, Lea County.

The well is 2310 feet (N.) (S.) of the South line and 2310 feet (E.) (W.) of the West line of Section 10

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is A. B. Baker

Address Eunice, New Mexico

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma

We propose to drill well with drilling equipment as follows:

Rotary Tools.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

| Size of Hole | Size of Casing | Weight Per Foot | New or Second Hand | Depth | Landed or Cemented | Sacks Cement |
|--------------|----------------|-----------------|--------------------|-------|--------------------|--------------|
| 15 1/2" | 13-3/8" | 44.5 | New | 200' | Cemented | 150 |
| 11 1/2" | 9-5/8" | 36# | New | 2800' | Cemented | 1000 |
| 8 1/2" | 7" | 23# | New | 5200' | Cemented | 400 |

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 5200 feet.

Additional information:

Halliburton process shall be used in cementing all casing.

Approved AUG 26, 1948, 19

except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name Skelly Oil Company

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

OIL & GAS INSPECTOR