

AREA 640 ACRES
LOCATE WELL CORRECTLYNEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

Skelly Oil Company **Tulsa, Oklahoma**
Company or Operator Address
Baker "B" Well No. **13** in **NE/4 SW/4** of Sec. **10**, T. **22S**
Lease
R. **37E**, N. M. P. M. **Paddock** Field, **Lee** County.
Well is **3300** feet south of the North line and **4290** feet west of the East line of **Sec. 10-22S-37E**
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is **A. B. Baker** Address **Emice, New Mexico**
If Government land the permittee is Address
The Lessee is **Skelly Oil Company** Address **Tulsa, Oklahoma**
Drilling commenced **October 14** 19 **48** Drilling was completed **November 17** 19 **48**
Name of drilling contractor **Makin Drilling Company** Address **Hobbs, New Mexico**
Elevation above sea level at top of casing **3419** feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from **5205** to **5230** No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
13-3/8	44.5	Welded	Arco	154	T.P.				
9-5/8	36	8R	Nat'l.	1732	Float				
9-5/8	36	8R	Rep.	1000					
7	23	8R	Spang	5275	Float		5205	5230	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
15 1/2	13-3/8	158	150	Halliburton		
11 1/2	9-5/8	2715	1000	"		
8 1/2	7	5230	350	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters — Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Mud Acid	500 gals.	11-13-48	5205-5230	

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **5230** feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **November 16** 19 **48**
The production of the first 24 hours was **184** barrels of fluid of which **80-90** % was oil; %
emulsion; **10-20** % **salt** water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

R. E. Lee Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this **26th**day of **January**, 19 **49**

R. E. Lee
Notary Public

MY COMMISSION EXPIRES AUG. 19, 1952
My Commission expires

Hobbs, E. Max **Jan. 26, 1949**
Place Date

Name **J. J. Smiley**Position **Dist. Supt.**Representing **Skelly Oil Company**
Company or Operator

Address

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	90	90	Surface Sand & Caliche
90	159	69	Red Bed & Shells
159	675	516	Shale & Red Bed
675	976	301	Red Bed
976	1118	142	Shale & Red Bed
1118	1270	152	Anhydrite
1270	1332	62	Salt
1332	2380	1048	Salt & Anhydrite
2380	2555	175	Anhydrite
2555	2621	66	Anhydrite & Lime
2621	3011	390	Anhydrite
3011	3230	219	Anhydrite & Lime
3230	3333	103	Lime
3333	3404	71	Anhydrite & Lime
3404	3770	366	Lime
3770	3830	60	Lime & Sand
3830	4716	886	Lime
4716	4985	269	Broken Lime
4985	5230	245	Lime