

BAKER B #14

PRESENT

13 3/8", 45#, @ 159' w/105  
sxs, 17" hole

8 5/8", 28#, @ 2800' w/800  
sxs, 11 1/4" hole

Paddock Perfs. (Squeezed)  
5093-98'  
5104-11'  
5120-31'

Drinkard Perfs.  
6408-72'

CIBP @ 6600'

Upper Ellenberger  
7460-78'

Retainer @ 7495'

5 1/2", 17#, @ 7545'  
cemented with 115 sxs  
around shoe, 450 sxs thru  
2-stage tool @ 7242', and  
175 sxs thru perf. @ 5850'

PROPOSED

13 3/8", 45#, @ 159'  
w/105 sxs, 17" hole

8 5/8", 28#, @ 2800'  
w/800 sxs, 11 1/4" hole

Paddock Perfs. (Squeezed)  
5093-98'  
5104-11'  
5120-31'

Blinebry Perf.  
(Proposed)  
5420-79'

5571'  
5291'

CIBP @ 5900' Proposed

Tubb Perfs. 598-611'  
(Proposed)

CIBP @ 6200' (Proposed)

Drinkard Perfs.  
6408-72'

CIBP @ 6600'

Upper Ellenberger  
7460-78'

Retainer @ 7495'

5 1/2", 17#, @ 7545'  
cemented w/115 sxs  
around shoe, 450 sxs  
thru 2-stage tool  
7242', and 175 sxs  
thru perf. @ 5850'