

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE O. C. C.

MISCELLANEOUS NOTICES

Nov 18 7 28 AM '63

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 15, 1963
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. **S. E. Long** Well No. **2** in **D** (Unit)
(Company or Operator)
NW $\frac{1}{4}$ **NW** $\frac{1}{4}$ of Sec. **11**, T. **22 S**, R. **37 E**, NMPM., **Paddock** Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 6545'
PB: 5225'
Csg: 9 5/8" @ 1110' w/600 sx., 7" @ 6545' w/800 sx.
Perfs: 6443-6455', 6471-6486' (Both sets squeezed), 5105-5150' (Paddock)

Propose to move in and rig up unit. Pull tubing. Set Ret. Bridge Plug @ 5050'. Run cement bond log 3500-4000'. If bond log indicates good cement over interval logged, run Isotron log 2300-5050'. If cement is not good block squeeze @ 3500' and 4000'. Re-run bond log. Perforate 7" csg. in Grayburg formation at interval indicated by above Isotron log w/1 JSPP. Sand oil frac. perfs. w/30,000 gals oil + 2#/gal 20/40 Ottawa sand + 1/40#/gal Adomite Mark II in 3 equal stages using RCN ball sealers between stages. Test and dual complete in Paddock & Penrose Skelly Pools.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By.....

Title.....

Socony Mobil Oil Company, Inc.

By.....
Company or Operator

Position.....
Group Supervisor

Send Communications regarding well to:

Name.....
Socony Mobil Oil Company, Inc.

Address.....
Box 1800, Hobbs, New Mexico