

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION WELL COMPLETION OR RECOMPLETION REPORT AND LOG

Well No.	1-1-77
State	☒ NM

Well No.	660	North	660	Lea
Company	Anadarko Production Company			Lou Wortham
Address	P. O. Box 806 Eunice, New Mexico 88231			Eunice, San Andres South

West	11	22S	37E	3378 DF	3378
8-9-46	9-5-46	1-9-85			
5175	4900			0-5175	

San Andres	3882' - 4308'	Unknown
Dual Spaced Compensated Neutron, Accoustic Cement GR.		No

CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB. FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT OF CEMENT
13 3/8"	48#	285'	Unknown	225 SX	-
8 5/8"	32#	2815'	Unknown	1500 SX	-
5 1/2"	17#	5113'	Unknown	500 SX	-

LINER RECORD				TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8	4700'	

ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
3882-4308	5600 gals 15% HCL Acid fraced w/ 40,000 gals 65% quality foamed HCL Acid (14,000 gals 20% HCL acid & 739,000 SCF Na.)

PRODUCTION							
Production Method (Flowing, gas lift, pumping - Size and type pump)						Well Status (Prod. or Shut-in)	
Pumping 2 1/2" X 2" X 16' Insert						Producing	
Date of Test	Time of Test	Shut-in Time	Flow Rate (bbl./hr)	Oil - Bbl.	Water - Bbl.	Gas - Bbl.	Gravity - API (Corr.)
1-12-85	8 hrs	-	93	31	71.33	171	2301
Flow Turn-off Test	Flowing Pressure	Shut-in Pressure	Flow Rate (bbl./hr)	Oil - Bbl.	Water - Bbl.	Gas - Bbl.	Gravity - API (Corr.)
			93	214	513		35.2

34. Location of well (Soil, used for fuel, vented, etc.)	Sold
35. Name of Attachment	Bob Shirley

1 copy ea. of Dual Spaced Comp. Neutron & Accoustic Cement Evaluation Log w/ GR.

I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1195.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>1090</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt <u>1179</u>	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt <u>2327</u>	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>2470</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers <u>2572</u>	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>3412</u>	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>3680</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>3806</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinebry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	370	370	Sand, Caliche, & redbeds				
370	1090	720	Redbeds				
1090	1179	89	Anhydrite				
1179	2327	1148	Salt & Anhydrite				
2327	3412	1085	Anhydrite, Lime, & Sand Stringers				
3412	3680	268	Lime, Dolomite, & Sand				
3680	3806	126	Dolomite				