
## DUPLICATE

NEW L AICO OIL CONSERVATION COMM. JON

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES



HORBS CARRIER

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

advisable, or the rejection by the Commission or a ed, and work should not begin until approval is obtithe Commission.  Indicate natu		tice by checking be		-
NOTICE OF INTENTION TO TEST CASING SHUT-OFF	x		NTION TO SHOOT TREAT WELL	OR
NOTICE OF INTENTION TO CHANGE PLANS			NTION TO PULL OR ALTER CASING	<u> </u>
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL		
NOTICE OF INTENTION TO DEEPEN WELL				
	Hobbs,	New Mexico	October	8, 1946 Date
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.  Gentlemen: Following is a notice of intention to do certain work The Chie Oil Company	Lo		Well No. 8	<sub>in</sub> <b>w</b> /4, <b>w</b>
Company or Operator Le	ase	N. M. P. M.,	Paddock	Fie
FULL DETAILS OF FOLLOW INSTRUCTIONS IN THE STATE TOTAL Depth 2802 - Anhydric 2796 cemented with 1500 Sa	RULES.	and regulations et 72 jts. 8-5/	S OF THE COMMISS	at
FOLLOW INSTRUCTIONS IN THE	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802' - Anhydric 2796' cemented with 1500 Salat 4:15 A.M. 10-8-46. Will	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will	RULES .  te. S  cks re  l test	and regulations et 72 jts. 8-5/ gular cement.	8" 32# Casing a	at wa
Total Depth 2802! - Anhydri 2796! cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will 4:15 A.M. 10-10-46. Now W.	te. S cks re l test O.C.	and REGULATIONS et 72 jts. 8-5/ gular cement. and drill plug	80FTHE COMMISS.  (8" 32# Casing a Plug pumped down at approximate	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will 4:15 A.M. 10-10-46. Now W.	te. S cks re l test O.C.	and REGULATIONS et 72 jts. 8-5/ gular cement. and drill plug	8" 32# Casing a	at wa
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will 4:15 A.M. 10-10-46. Now W.	te. S cks re l test O.C.	and regulations  et 72 jts. 8-5/ gular cement.  and drill plug  The Oh  By  Position  Su	SOF THE COMMISS.  (8" 32# Casing a Plug pumped down at approximate	at m oly
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will 4:15 A.M. 10-10-46. Now W.	te. S cks re l test O.C.	The Oh  Position  Send communications  Send communi	SOF THE COMMISS.  (8" 32# Casing a Plug pumped down at approximate  at approximate  company or Operator  pt.  nunications regarding	at was ally
Total Depth 2802' - Anhydri 2796' cemented with 1500 Sa at 4:15 A.M. 10-8-46. Will 4:15 A.M. 10-10-46. Now W.	te. S cks re l test O.C.	The Oh  Position Send community  Name The Oh	SOF THE COMMISS.  (8" 32# Casing a Plug pumped down at approximate	g well to

10/4 to 10 miles in

t 新 ( ) provide the form of the provide that the form of the for