

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

RECEIVED
OCT 10 1945
HOBBSS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHUT-OFF CHEMICALLY TREAT WELL	xx
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		do to perforate Csg. & cement off perforations	xx

Hobbs, New MexicoOct. 9, 1945

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Repollo Oil Company Alexander Rodgers Well No. 2 in NE NE
Company or Operator Lease
of Sec. 12, T. 22S, R. 37E, N. M. P. M., Paddock Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

TD 5300'

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

8/23/45- Drilled cement to 5250'- Perforated casing f/ 5200 to 5230- 180 holes
8/25/45- Cemented Perf. f/ 5200 to 5230 w/ 25 Sacks, Halliburton w/ 1000# on Csg. WOC
8/27/45- Perforated f/ 5130 to 5170 w/ 160 holes
8/28/45- Acidized f/ 5130 to 5170 w/ 2000 Gal. Acid.
8/31/45- Cemented Perf. f/ 5130 to 5170 w/ 50 Sacks Inscr, Halliburton w/ 1000# on Csg.
9/9/45 - Perforated f/ 5245 to 5260 w/ 90 holes & Acidized w/ 1000 Gal. Acid.
9/11/45- Cemented Perforation f/ 5245 to 5260 w/ 35 Sks. Inscr, Halliburton w/ 3500# on
9/16/45- Re-cemented " 5245 to 5260 w/ 25 Sks. Com. do 1000# do Csg.
9/21/45- Perforated f/ 5190 to 5210 w/ 120 holes &
9/22/45- Acidized w/ 2000 Gal. Acid f/ 5190 to 5210.
9/25/45- Cemented Perf. f/ 5190 to 5210 w/ 50 Sks. Com. Halliburton w/ 1000# on Csg.
9/30/45- Perforated Casing f/ 5185 to 5189 w/ 12 holes
10/1/45- Perforated Casing f/ 5179 to 5188 w/ 24 holes.
10/1/45- Acidized w/ 2000 Gal. Acid f/ 5179 to 5189.

Approved OCT 10 1945, 19____
except as follows:

Repollo Oil CompanyBy J. B. Rhessa
Company or OperatorPosition Dist. Supt.

Send communications regarding well to

Name J. B. Rhessa,Address Hobbs, N.M.

OIL CONSERVATION COMMISSION,
By Roy Yarbrough
Oil & Gas Inspector
Title _____

