

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 3rd, 1948

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Samedan Oil Corporation
Company or Operator

Lease Well No. 2 in the _____

SW-1/4 of the SW-1/4 of Sec. 14, T. 22, R. 37, N. M. P. M.,
Drinkard Field, _____ County.

The dates of this work were as follows: _____

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on _____ 19____
and approval of the proposed plan ~~was~~ (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

- 8-1-48 Lane Wells perforated 7" 23# Casing 5-holes from 6413 to 6411
8-4-48 Halliburton set Baker model K Retainer and tested Perforations in Casing at 6410 w/4000#
8-5-48 Halliburton Squeeze Perforations at 6428 w/ 50 sacks cement to 5000# Pressure
8-11-48 Lane Wells Perforations 7" 23# Casing 72-Holes from 6446 to 6428 - 16-holes from 6424 to 6420
8-14-48 Acidized w/ 500 gallons acid Casing Perforations 6420-to 6446 Tubing Perforations 6443 to 6446 20% Acid used
9-3-48 Acidized w/500 gallons 15 % acid Casing perforated 6420 to 6424 Tubing 6424
9-4-48 Acidized w/1000 gallons 15 % Acid Tubing perforations 6424

Witnessed by _____

Name

Company

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

24 day of Nov 1948

Name E. J. Cook

Position Supt.

Notary Public

Representing Samedan Oil Corporation
Company or Operator

My commission expires 8-28-52

Address _____

Remarks:

See Reverse side for Further work done on well

Name _____

Supt. _____

Title _____

9-6-48 Acidized w/ 2000 gallons of 15% Acid Tubing Perforation 6424
9-13-48 Acidized w/ 200 gallons of Acid Tubing perforations 6424-6420
Installed pumping equipment Well Pumping 3/4" rods 1-1/4" Pump 54" Stroke
8 strokes per min. 6300' - 3/4" rods.

Well making 64 bbls. in 24 hrs. during Test October 23rd. 1948