

Form C-103
DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
MAY 15 1947
REGISTRY
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

May 13, 1947

Date

Monument, New Mexico.

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Amerada Petroleum Corporation E. W. Walden Well No. 2 in the
Company or Operator Lease

NE 1/4 SW 1/4 of Sec. 15, T. 22S, R. 37E, N. M. P. M.,
Drinkard Field, Lea County.

The dates of this work were as follows: May 12, 1947

Notice of intention to do the work was (~~xxxx~~) submitted on Form C-102 on May 10, 19 47
and approval of the proposed plan was (~~xxxx~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6470' Total Depth Lime, nipped up and picked up 2" Tubing and found top of cement 6340' tested casing with 1000# for 30 minutes and was OK, drilled out cement to 6465', tested casing with 1000# for 30 minutes and was OK, Measured tubing out of hole Correction 6465 equals 6466'. Drilled out depth should be 6466'. Gun perforated from 6425 to 6460' with 140 holes, set 2" EUE 4.7#, J-55, R-2, 8 RT Spang SS Tubing at 6461' with 1-3' perforated nipple on bottom bull plugged and 2-6' Subs on top, displaced mud with 160 Barrels oil.

Witnessed by K. V. Stephenson Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

13 day of May, 19 47

Name Don Joppa

Will Haire Taylor
Notary Public

Position Asst. Dist. Supt.

Representing Amerada Pet. Corp.
Company or Operator

My commission expires _____
My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date MAY 15 1947

Roy Yunkrough
Oil & Gas Inspector
Title