

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/> XX
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name E.W. Walden
3. Address of Operator Drawer "D", Monument, New Mexico 88265	9. Well No. 3
4. Location of Well UNIT LETTER <u>N</u> , <u>729</u> FEET FROM THE <u>South</u> LINE AND <u>2053</u> FEET FROM THE <u>West</u> LINE, SECTION <u>15</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM.	10. Field and Pool, or Wildcat Brunson-Ellenburger
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input checked="" type="checkbox"/> XX	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pulled production equipment, set RBP at 4709' w/2 sks sand on top, perforated 5½" csg., 2 holes at 4324'. Squeezed 5½" csg. perfs at 4324' w/300 sks. 50-50 Pos Mix cement, mixed with 2% calcium chloride. West Engineering tagged top of cement in 5½" csg. at 4192', ran temperature survey from 1,000' to 4192' found est. top of cement outside of 5½" csg. at 4110'.

Perforated 5½" csg. w/2 holes at 3960'. Squeezed 5½" csg. perfs. at 3960' w/300 sks. 50-50 Pos Mix cement w/2% cal. chloride. West Eng. Co. tagged top of cement in 5½" csg. at 3796'. Ran temperature survey found top of cement at 3560' outside 5½" csg.

Perforated 5½" csg. w/2 holes at 3400'. Squeezed 5½" csg. perfs at 3400' w/300 sks. 50-50 Pos Mix cement w/2% cal. chloride. West Eng. Co. tagged top of cement inside 5½" csg. at 3260'. Ran temp. survey from surface to 3260' found est. top of cement outside 5½" csg. at 1940'. Survies Witnessed by NMOCC.

Drilled and cir. good cement from 3260' to 3400', 3796' to 3860', 3860' to 3968', 4192' to 4328'. Pulled RBP. Ran production equipment and resumed production. No change in status.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>[Signature]</u>	TITLE <u>Supver., Admin. Services</u>	DATE <u>10-8-75</u>
<p>Oil & Gas Insp.</p>		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		