

**DUPLICATE**

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

**RECEIVED**  
AUG 7 1947  
**RECEIVED**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning of operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

August 4, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

E. W. Walden

Well No. 3 in the

Company or Operator

Lease

SE 1/4 SW 1/4

of Sec. 15

T. 22S

R. 37E

, N. M. P. M.,

Brunson

Field, Lea

County.

The dates of this work were as follows:

August 3, 4, 5, 1947

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on August 1 19 47  
and approval of the proposed plan was (~~obtained~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7875' Total Depth, Granite. 7872' Drilled Out Depth. Ran Temperature survey and found top of cement at 4474', 83% of calculated fill. Picked up tubing, went in hole, found top of cement at 7515', tested casing with 1000# for 30 minutes and was OK. Drilled out cement to 7872', tested casing with 1000# for 30 minutes and was OK. Gun perforated from 7700' to 7868' with 4 shots per foot, 672 shots. Ran 251 jts. of 2" EUE, 4-7#, J-55, R-2, 8-RT SS Tubing New and swung at 7862' with 1-3' perf. nipple on bottom bull plugged and 1-8', 1-6' and 2-4' subs on top. Displaced mud with 175 barrels of oil.

Witnessed by <u>D. F. Furse</u>	<u>Amerada Petroleum Corporation</u>	<u>Foreman</u>
Name	Company	Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

4th. day of August, 19 47

Name Walter James

Position Farm Boss

W. H. Taylor  
Notary Public

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires My Commission Expires May 6, 1948

Address Drawer D, Monument, New Mexico

Remarks:

**APPROVED**  
AUG 1 1947

Roy Garbrough  
Name  
Title