

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

FILED
JUL 21 1947
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

July 17, 1947

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

E. W. Walden

Well No. 4

in the _____

Company or Operator

Lease

NW 1/4, SW 1/4

of Sec. 15

T. 22S

R. 37E

N. M. P. M.,

Brunson

Field,

Lea

County.

The dates of this work were as follows: _____

July 16, 17, 1947

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on July 13, 19 47

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

7917' Total Depth Granite (4' Correction from 7913') Ran Temperature Survey and found top of cement at ~~25~~ 3450', 83% of calculated fill. Nipped up and went in hole with tubing and found top of cement at 7803' and tested casing with 1000# for 30 minutes and was OK. Drilled out cement to 7917' and tested casing with 1000# for 30 minutes and was OK. Gun perforated with McCullough 7794' to 7910', 464 shots. Ran 258 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, Spang SS Tubing and set at 7905' with 1-3' perforated nipple on bottom bull plugged and 2-8' and 1-4' subs on top. Displaced mud with oil, 175 barrels. Ran 20 bbls. of water ahead of oil.

Witnessed by K. V. Stephenson

Name

Amerada Petroleum Corp.

Company

Foreman

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

17th. day of July, 19 47

Name

Position

Asst. Dist. Supt.

Representing Amerada Petroleum Corp.

Company or Operator

My commission expires _____

My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date JUL 21 1947

Roy. Yarbrough
Name
Oil & Gas Inspector
Title