

# OIL CONSERVATION COMMISSION

## DUPLICATE MISCELLANEOUS REPORTS ON WELLS

Santa Fe, New Mexico

SEP 10 1947  
RECEIVED  
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

September 7, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the  
Amerada Petroleum Corporation E. W. Walden Well No. 5 in the  
 Company or Operator Lease  
NW 1/4 SW 1/4 of Sec. 15, T. 22S, R. 37E, N. M. P. M.,  
Brownson Drain Field Field, Lea County.

The dates of this work were as follows: September 5, 6, 1947.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on September 2, 19 47  
 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6475' Total Depth, Lime. 6473' Drilled Out Depth. Ran temperature survey and found top of cement at 2900', 87% of calculated fill. Nippled up 5 1/2" casing, picked up tubing, went in hole with 4-3/4" bit and drilled out cement from 6392' to 6473'. Tested casing with 1000# for 30 minutes before and after drilling cement and was OK. Perforated with Lane Wells from 6432'- 6472', 160 shots. Ran total of 206 joints of 2" EUE, 4.7#, J-55, R-2, 8-RT, Spang and Pittsburg SS Tubing (bottom 5 jts. second hand) with 2-8' and 1-4' nipples on top and 1-3' perforated nipple on bottom bull plugged and swung at 6469'. Displaced mud with 150 barrels of oil and started swabbing at 12 noon 9-6-47. In 19 hrs, flowed and swabbed 138.69 bbls. oil, 2/10% BS, no water.

Witnessed by K.V. Stephenson Name Amerada Petroleum Corporation Company Foreman Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

7th. day of September, 19 47

Name Don Lipp

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires My Commission Expires May 9, 1949

Address Drawer D, Monument, New Mexico

Remarks:

**APPROVED**  
SEP 10 1947

Roy Garbrough  
Name  
Title  
OIL & GAS INSPECTOR