


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

DUPLICATE

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Squeezing Well	X

December 11, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

SHEET #1

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
**Amerada Petroleum Corporation** **E. W. Walden** Well No. **6** in the \_\_\_\_\_  
 Company or Operator Lease  
**SW $\frac{1}{4}$  SW $\frac{1}{4}$**  of Sec. **15S**, T. **22S**, R. **37E**, N. M. P. M.,  
**Brunson** Field, **Lea** County.

The dates of this work were as follows: **December 7 - 11, 1947**

Notice of intention to do the work was (~~approved~~) submitted on Form C-102 on **December 6,** 19 **47**  
 and approval of the proposed plan was (~~approved~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**6472'** Drilled Out Depth, **6445'** Top of Plastic Cap. Killed well, pulled tubing and dumped pea gravel down hole for 22' fill from **6472'** to **6450'**. Ran 5 gals. Dowell Plastic for cap from **6450'** to **6445'**. Set Baker Retrievable Retainer at **6421'** and pumped in 8 bbls. of water and formation broke at 900#. Pumped in 150# of Calcium Chloride and then 100 gallons of Dowell Plastic mixed 50 gals. with filler and 50 without. Squeezed into formation with 2100# max. press. and complete at 4:45PM, 12-7-47. Pulled up 110' and reversed out  $\frac{1}{2}$  bbl. plastic. At end of 11 hrs. tested plastic and pumped 5 bbls. water into formation with 1300#. Plastic job no good. Re-ran plastic job with 5 bbls. water first at 1300#, 150# Calcium Chloride and 100 gals. Dowell Plastic mixed 50 gals. with filler and 50 without. Witnessed by **D.W. Gordon** **Amerada Petroleum Corp.** **Farm Boss** (Cont'd. on Sheet #2)

Name

Company

Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

11th. day of **December**, 19 **47**

Name

Position

**Asst. Dist. Supt.**

Representing

**Amerada Petroleum Corporation**  
Company or Operator

My commission expires \_\_\_\_\_

My Commission Expires May 9, 1948

Address

**Drawer D, Monument, New Mexico**

Remarks:

APPROVED

DEC 15 1947

**Roy Yach**  
Name  
OIL & GAS INSPECTOR  
Title