

Form C-102
DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
DEC 8 1947
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Squeezing Well	X

December 5, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation E. W. Walden Well No. 6 in the
Company or Operator Lease

SW $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 15, T. 22S, R. 37E, N. M. P. M.,
Brunson Field, Lea County.

The dates of this work were as follows: December 2, 3, 4, 5, 1947

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on November 30, 19 47
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6472' Drilled Out Depth. Pulled tubing and packer and ran Lane Wells Gamma Ray Survey. Set Baker Model K Cement Retainer at 6444' and pumped 30 bbls. water into formation ahead of cement w/1300#. Squeezed 40 sacks of Trinity Common Cement into formation, final pressure 3200#. Pulled up to 6444' and reversed out about 1-3/4 bbls. cement. Drilled out cement from 6444' to 6472' and perforated from 6437' to 6470', 132 holes. Ran American Hook Wall Packer and 207 jts. of 2" EUE Tubing, displaced mud with 160 bbls. of oil and set Packer at 6359' with bottom of tubing at 6467'. Started swabbing and in 8 1/2 hrs. to 1:00PM, 12-5-47, swabbed 29 bbls. of fluid, the last two hours 90% BS.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Farm Boss
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

5th. day of December, 19 47

Name Don Taylor

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires My Commission Expires May 8, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

DEC 8 1947

Date

Ray Yorknough
Name
Title