

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
DEC 2 1947
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

| | | | |
|--|--|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | | REPORT ON REPAIRING WELL | |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | | REPORT ON PULLING OR OTHERWISE ALTERING CASING | |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | | REPORT ON DEEPENING WELL | |
| REPORT ON RESULT OF PLUGGING OF WELL | | Report on Plugging Back | X |

November 29, 1947

Monument, New Mexico
Date Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation E. W. Walden Well No. 6 in the _____
 Company or Operator Lease
SW $\frac{1}{4}$ SW $\frac{1}{4}$ of Sec. 15, T. 22S, R. 37E, N. M. P. M.,
Brunson Field, Lea County.

The dates of this work were as follows: November 26-29, 1947

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on November 26, 19 47
 and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED
6510' Plugged Back Depth, 6520' Drilled Out Depth. Set Baker Model K Bridging Plug at 6570' and dropped 20 sacks of Incor Cement on top of plug. Pulled up to 6510' and reversed out about 2 bbls. cement. Drilled out cement from 6510' to 6520' and perforated with Lane Wells from 6454' to 6490', 144 holes. Ran Lane Wells Packer and 208 jts. of 2" EUE, 4.7# Tubing, displaced mud with 140 bbls. of oil and set Packer at 6394' w/1-3' perf. sub on ~~bottom~~ bottom of tubing at 6490'. Started swabbing and in 27 hrs. to 6:00AM, 11-29-47, swabbed 36.08 bbls. fluid, 35% to 80% water. Water tested 6000ppm Chloride.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Farm Boss
 Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

29th. day of November, 19 47

Name Don Trapp

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
 Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED
DEC 2 1947

Date _____

Roy Garbrough
 Name
 OIL & GAS INSPECTOR
 Title