

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

NOV 21 1947

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

November 15, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Amerada Petroleum Corporation

E. W. Walden

Well No. 6

in the

Company or Operator

Lease

SW $\frac{1}{4}$ SW $\frac{1}{4}$

of Sec. 15

T. 22S

R. 37E

N. M. P. M.,

Brunson

Field, Lea

County.

The dates of this work were as follows:

November 14, 15, 1947

Notice of intention to do the work was ~~(amended)~~ submitted on Form C-102 on November 11, 1947
and approval of the proposed plan was ~~(amended)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8090' Total Depth, Line, 8088' Drilled Out Depth. Ran temperature survey and found top of cement at 3542', 84.1% of calculated fill. Nipped up 52" Casing, drilled out cement from 7984' to 8088' and tested casing with 1000# for 30 minutes before and after drilling cement and was OK. Perforated with McGullough from 7990' to 8085', 380 holes. Ran 260 joints of 2" EUE, 4.7#, J-55, R -2, 8-RT, SS Tubing New and swung at 8082' with 1-3' perforated nipple on bottom bull plugged and 1-4' sub on top. Displaced mud with 180 barrels of oil.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

15th day of November, 1947

Name Don TaylorPosition Asst. Dist. Supt.Representing Amerada Petroleum Corporation
Company or OperatorMy commission expires My Commission Expires May 9, 1948Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

NOV 21 1947

Ray Yarkrough
Name
OIL & GAS INSPECTOR
Title