

**DUPLICATE**  
**OIL CONSERVATION COMMISSION**  
 Santa Fe, New Mexico  
**MISCELLANEOUS REPORTS ON WELLS**

**RECEIVED**  
 NOV 26 1947  
**HOBBS OFFICE**

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<b>X</b>	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL		

November 24, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
 SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation E. W. Walden Well No. 7 in the \_\_\_\_\_  
 Company or Operator Lease

SE 1/4 SW 1/4 of Sec. 15, T. 22S, R. 37E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: November 20 - 24, 1947

Notice of intention to do the work was (~~submitted~~) submitted on Form C-102 on November 18, 19 47  
 and approval of the proposed plan was (~~submitted~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6475' Total Depth, Line. 6470' Drilled Out Depth. Ran temperature survey and found top of cement at 3308', 76.9% of calculated fill. Drilled out cement to 6470' and tested csg. with 1000# for 30 minutes before and after drilling cement and was OK. Perforated from 6452' to 6470', 72 holes. Ran 206 jts. of 2" EUE, 4.7#, J-55, R-2, 8-RT, SS Tubing New and swung at 6465' with 1-3' perf. sub on bottom bull plugged and 1-10' and 2-8' subs on top. Displaced mud with 145 bbls. of oil and in 14 1/2 hours well flowed and ~~was~~ swabbed 130 bbls. pipe line oil. Well put on 1/4" pos. choke and in 20 hours flowed 107.64 bbls. pipe line oil, gravity 39.8 corrected. Gas volume 102M per day, Gas-Oil-Ratio 790. Well completed.

Witnessed by K. V. Stephenson Amerada Petroleum Corporation Foreman  
 Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

24th. day of November, 1947

Name Don Topp

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
 Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico

Remarks:

**APPROVED**

Date NOV 26 1947

Roy Yackrowich  
 Name  
Oil & Gas Inspector  
 Title