

**DUPLICATE**

# **OIL CONSERVATION COMMISSION**

Santa Fe, New Mexico

## **MISCELLANEOUS REPORTS ON WELLS**

NOV 24 1947  
RECEIVED  
HOODS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	<b>X</b>

November 19, 1947

Date

Monument, New Mexico

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
Amerada Petroleum Corporation E. W. Walden Well No. 7 in the \_\_\_\_\_  
Company or Operator Lease  
SE 1/4 SW 1/4 of Sec. 15, T. 22S, R. 37E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: November 18, 19, 1947

Notice of intention to do the work was (~~was~~) submitted on Form C-102 on November 18, 19 47  
and approval of the proposed plan was (~~was~~) obtained. (Cross out incorrect words.)

### **DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED**

6475', Total Depth, Lins. Ran Schlumberger Survey. Ran 163 joints of 5 1/2" OD, 15.5#, J-55, R-3, 8-RT, Reg. T/G, SS Casing New and set at 6475'. Cemented with 450 sacks of El Toro Regular Bulk Cement and 50 sacks of Incor Cement and plug pumped to 6390' at 2:30AM, 11-19-47. Final pressure 1400#. Five Larkin Centralizers set at: 6340', 6370', 6400', 6430', 6460'.

Witnessed by E. D. W. Gordon Amerada Petroleum Corporation Farm Boss  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

19th day of November, 19 47

Name E. W. Walden

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

**APPROVED**

Date NOV 24 1947

Roy Yankovich  
Name  
OIL & GAS INSPECTOR  
Title