

Form 9-331
Dec. 1973Form Approved.
Budget Bureau No. 42-R1424UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR
CONOCO INC.3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 882404. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 2130' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐

5. LEASE

LC-032573 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

NMFU

8. FARM OR LEASE NAME

Elliot A-15

9. WELL NO.

3

10. FIELD OR WILDCAT NAME

Brunson Ellenburger

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 15, T-22S, R-37E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-1-80 MIRR. Pool w/ rods & pump. Tag fill 7739'. Pool w/ tbg. CO to 7788'. Spot 5666 15% HCl-NE. Flush w/ 40666 KCL wtr. Pool w/ tbg. w/ tbg & pkr at 7600'. Acidize w/ 2730 gals 15% HCl-NE-FE. Divert w/ 500# rock salt, 350 gals. 10# brine water w/ 30#/1000 gals guar gum. Pump 2730 gals. 15% HCl-NE-FE. Flush w/ 50666 KCL TFW. Scale inhibit w/ 2 drums Unichem Tt-814 in 20666 2% KCL TFW. Flush w/ 80666 TFW. Divert w/ 500# rock salt, 350 gals 10# brine w/ 30#/1000 gals. guar gum. Ran tbg set at 7768', SN at 7742'. Tested well 10/23/80, made 1080, 198W, w/ gas TSTM.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Wm G. Dutton

TITLE Administrative Supervisor

DATE

10/29/80

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD

NOV 3 1980

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICOUSGS 5
NMFU 4
file