

Elliot A-15 #1
Well History

Location: 1650' FSL, 2310' FEL, Sec 15, T-22-S, R-37-E, Lea County,
New Mexico

Elevations: DF 3392' GL 3382'

TD: 7690'

Casing: 10-3/4", 32.75# @ 191', cmt w/125 sx, cmt circ. to surface
7-5/8", 24# @ 2801', cmt w/1450 sx, cmt circ. to surface
5 1/2", 17# @ 7603', cmt w/481 sx, TOC @ 3070' (survey)

Original Completion: 2-17-48 Perf Ellenburger 7516-45' and 7550-86'. Acidized
perfs w/500 gals 15% HCL. Acidized perfs 7516-86 w/1500
gals 15% HCL. Acidized 7603-90' w/1500 gals 15% HCL.
IP: F 250 BO in 5 hrs.

Workovers: 2-3-50 Acidized perfs 7603-90' w/1500 gals 15% regular acid.
Swabbed 77 BO in 15 hrs.

7-7-66 Acidized 7516-86' and 7603-90' w/5000 gals 15% NEHCL & 800
lbs salt. P/24 hrs 19 BO, 13 BW, 221 MCF.

9-16-69 Spot 25 sx cmt plug 7450-7600. Set CIBP @ 3960' w/1 sx cmt
on top. Ran GR-N log 3900-2400' and perf 3648-3855' w/32 1/2"
holes. Frac w/2,000 gals 15% HCL, 40,000 gals Mod br plus
60,000 lb 20/40 sd.
Test: P/24 hrs: 66 BO, 165 BW, 40 MCF.

6-20-84 Perf Paddock 5133-5153. Acdz w/2000 gals 15% NEFE. Swab
1 BO, 35 BLAW, 105 BW in 7 hrs. Sqz w/100 sxs cmt. Perf
Paddock 5065-5083 and 5095-5125, 1 SSPF. Acdz w/5000 gals
15% NEFE. Test 24 hrs. pumping 5 BO, 62 BW, 23 MCF under
a packer. Grayburg perfs 3648-3855 isolated by packer.