

007-5115

- 9-8 WOC.
- 9-9 RAN 4 3/4" BIT, 6 DC'S & 2 3/8" TBG TO 3395'. TAGGED RET & TSTD CSG TO 1000# FOR 15 MINS, HELD OK. DRLG RET & CMT. CIRC HOLE CLEAN.
- 9-10 DRLD 23' CMT, WASHED TO 3750'. TSTD CSG, 1200# FOR 30" HELD OK. DRLD RET @ 3750', 12' CMT, CIRC HOLE CLEAN.
- 9-11 POH, CHANGED BIT, GIH, DRLD 54' CMT, WASHED TO 4500'. TSTD CSG TO 1100# FOR 30", HELD OK. POH & LAYED DOWN DC'S.
- 9-12 RAN RETRIEVING TOOL, CIRC 20' SD OFF BP, DISPLACED CSG W/TRTD WATER. POH W/RBP. RAN 1 JT TBG, SN, 2 JTS TBG, GUIBERSON KVL-30 PKR W/AUTOMATIC JAY, PIPE @ 5975'. PKR. SET W/13 PTS COMPRESSION.
- 9-13 SWB 6 HRS. REC 25 BW. SLIGHT GAS @ END OF SWBG.
- 9-15 TURN DOWN SALES LINE.