

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBBS OFFICE OCC

## MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) <b>Repair csg. leak</b> <b>X</b>		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)April 23, 1956  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation R. E. Cole "A" Well No. 3 in I  
(Company or Operator) (Lease) (Unit)  
NE 1/4 SE 1/4 of Sec. 16, T. 22-S, R. 37-E, NMPM., Panrose-Skelly Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to increase production, it is proposed to repair casing leak as follows:

1. Pull tubing.
2. Set magnesium birdge plug on electric line in base of oil string. Dump one sack cement on plug.
3. Run tubing with HRC tool and pressure test casing at various depths.
4. Run 2-3/8" tubing with cement retainer set above leak. Attempt to cement through retainer, if cement circulates, closed bradenhead and perform bradenhead squeeze.
5. Drill out retainer and cement and pressure test casing. If casing is OK, clean out to total depth. Run 2-3/8" tubing and return well to production.

Approved....., 19.....  
Except as follows:Approved  
OIL CONSERVATION COMMISSIONBy.....  
Title.....Gulf Oil Corporation  
Company or Operator

By.....

Position.....  
Send Communications regarding well to:

Name.....

Address.....