Form C-103 Santa Fe, New Mexico MISCELLANEOUS REPORTS ON WELLS

Sumbit this report in triplicate to the Oil Conservation Commission or its proper agent within **HOBBS** to The loss specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERA-	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	9-5/8 REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	
	October 10, 1947 Hobbs, New Mexico Date Place
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:	
Gulf Oil Corporation	ts obtained under the heading noted above at the
Company or Operator	Lease
The second	*
	County. Loctober 6, 1947; tested October 9, 1947.
Notice of intention to do the work was (was intention)	submitted on Form C-102 on Cetober 7. V 1947
DETAILED ACCOUNT OF V The hole was washed down and t SO minutes. The plug was drilled and for SO minutes. Both tests were OK,	WORK DONE AND RESULTS OBTAINED the casing tested with 1800f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbswugh, State Oil
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were OK, and Gas Inspector, preparations were Top of cement back of 9-5/8"	WORK DONE AND RESULTS OBTAINED the easing tested with 1800f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbssugh, State Oil made to drill ahead. Sasing is 1500' per temperature survey.
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were OK, and Gas Inspector, preparations were Top of cement back of 9-5/8"	WORK DONE AND RESULTS OBTAINED the casing tested with 1200f pressure applied to the casing tested with 1200f pressure applied and after approval of Mr. Yarbssugh, State 011 made to drill ahead.
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were CK, and Gas Inspector, preparations were Top of cement back of 9-5/5" of Comment back of 9-5/5" of	WORK DONE AND RESULTS OBTAINED the easing tested with 1200f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbssugh, State Oil made to drill ahead. Company Drilling Foreman Company Title I hereby swear or affirm that the information given above is true and correct.
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were OK, and Gas Inspector, preparations were Top of cement back of 9-5/8" of Witnessed by G. Stach Gulf Name Subscribed and sworn before me this	WORK DONE AND RESULTS OBTAINED the easing tested with 1200f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbssugh, State Oil made to drill ahead. Company Drilling Foreman Company Title I hereby swear or affirm that the information given above
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were OK, and Gas Inspector, preparations were Top of cement back of 9-5/8" (Witnessed by G. Stash Gulf Name	WORK DONE AND RESULTS OBTAINED the easing tested with 1200f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbssugh, State Oil made to drill ahead. Company Title I hereby swear or affirm that the information given above is true and correct.
The hole was washed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were OK, and Gas Inspector, preparations were Top of cement back of 9-5/8" (Witnessed by G. Stash Gulf Name	WORK DONE AND RESULTS OBTAINED the easing tested with 1200f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Yarbosugh, State Oil made to drill ahead. Company Company Title I hereby swear or affirm that the information given above is true and correct. Name Position District Sup't. Representing Gulf Oil Corporation
The hole was weshed down and to so minutes. The plug was drilled and for 30 minutes. Both tests were CK, and Gas Inspector, preparations were Top of cement back of 9-5/8" of Witnessed by G. Steeh Gulf Name Subscribed and sworn before me this	WORK DONE AND RESULTS OBTAINED the easing tested with 1200f pressure applied for the casing tested with 1200f pressure applied and after approval of Mr. Tarbusugh, State Oil made to drill ahead. Company Title I hereby swear or affirm that the information given above is true and correct. Name Position District Sup*t.