

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

2040 South Pacheco
Santa Fe, NM 87505

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.	30-025-10326
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-3480
7. Lease Name or Unit Agreement Name	Cole State
8. Well No.	6
9. Pool name or Wildcat	Eumont YSRQ

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator Zia Energy, Inc.	3. Address of Operator PO Box 2510, Hobbs, NM 88241
4. Well Location Unit Letter B 660 Feet From The North Line and 1980 Feet From The East Line Section 16 Township 22S Rang. 37E NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3417' DF	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:		
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/19/98 Set CIBP @ 3588' (Witnessed by Buddy Hill of OCD). Dumped 35' Class 'C' cement on CIBP. Set CIBP @ 3400'. Circulate hole with 10 lb brine with 25 lb gel per bbl. Spot 25 sxs cement from 3400-3154.

8/20/98 Squeeze 25 sxs cement with 2% CaCl from 950-1190'. Squeezed 40 sxs cement with 2% CaCl from 183-400'. Tag plug at 183'. Spot 10 sxs @ 31' to surface. Cut off wellhead 3' below surface, weld on cap and dry hole marker.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Scott Nelson TITLE Engineer DATE 9/1/98

TYPE OR PRINT NAME Scott Nelson 393-2937 TELEPHONE NO.

(This space for State Use)

APPROVED BY [Signature] TITLE OIL & GAS INSPECTOR DATE OCT 3 1998

CONDITIONS OF APPROVAL, IF ANY:

SCW

9/1/98
dp