

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 South Pacheco
Santa Fe, NM 87505

WELL API NO.
30-025-10329

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-934

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

7. Lease Name or Unit Agreement Name

Adobe State

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER Shut In

2. Name of Operator
Zia Energy, Inc.

8. Well No.
3

3. Address of Operator
PO Box 2510, Hobbs, NM 88241

9. Pool name or Wildcat
Eumont

4. Well Location
Unit Letter L | 1980 Feet From The South Line and 660 Feet From The West Line

Section 17 Township 22S Rang. 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3411' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

A RBP was set at 3010' and tested to 500 psi.

- 1) Circulate hole with salt gel mud consisting of 10 ppg brine w/ 25 lbs gel/bbl.
- 2) Spot 25 sx class 'C' neat at 3010' to 2648'.
- 3) Spot 25 sx at 880' to 520'. POH with tubing.
- 4) Perforate 2 holes at 406'. Pump 25 sxs down casing and flush with 5 bbls. Surface casing shoe plug at 406 to 292'. WOC and tag.
- 5) Perforate 2 holes at 38'. Pump 10 sx cement.
- 6) Cut casing off 3' below surface and weld on dry hole marker.
- 7) Cut off anchors and clean location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Scott Nelson

TITLE

Engineer

DATE 5/16/00

TYPE OR PRINT NAME

Scott Nelson

393-2937

TELEPHONE NO.

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL: IF ANY
THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED.

dp