

JUN 17 1935

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

U. S. Land Office
Las Cruces

Serial Number 032573

Lease or Permit Permit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT RECORD OF SHOOTING.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	RECORD OF PERFORATING CASING.....	
NOTICE OF DATE FOR TEST OF WATER SHUT-OFF.....	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING.....	
REPORT ON RESULT OF TEST OF WATER SHUT-OFF.....	NOTICE OF INTENTION TO ABANDON WELL.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF ABANDONMENT.....	X
NOTICE OF INTENTION TO SHOOT.....	SUPPLEMENTARY WELL HISTORY.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

E.M.Elliott # 1.

Hobbs N.M. 6-14-35, 19

Following is a ~~report of work done~~ on land under ~~permit~~ described as follows:
New Mexico Lea S.E. New Mexico

(State or Territory) (County or Subdivision) (Field)
Well No. 1 SW/4 Sec. 17 22-S 37E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

The well is located 1980 ft. ~~N~~ of S line and 1980 ft. ~~E~~ of W line of sec. 17

The elevation of the derrick floor above sea level is 3400 ft.

Inspected by Thomas G. Taylor July 9, 1935.

DETAILS OF PLAN OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

Well Drilled to T.D. of 4077'. on May 31st, well plugged back with 74 sacks of cement from 4077 to 3750'. and Tested at this point for 5 days, showed no oil, gas or water. 7-5/8" casing set in this well at 2578' and cemented with 350 sacks. On June 8th plugging operations were started, Circulated hole with 11 lb mud, and the set bridge at 2578' and pumped in 25 sacks of cement, cement plug coming up to 2470' steel line measurement. Circulated hole with mud and shot off 7-5/8" casing at 786' and pulled same. Set bridge at 816' and pumped in 25 sacks of cement, bottom of cement plug 816' top of cement 756'. Filled hole to Surface with mud and cemented top of surface pipe with 10 Sacks of cement. Cellar filled and 4" pipe Marker cemented extending 4' above the surface of Ground, Pits filled and location restored to its original level. Plugging completed June 12th. Casing left in hole 252' of 10" casing. 1792' of 7-5/8" Casing.

Approved July 11, 1935

Company Continental Oil Co.

(Date)
Ernest A. Hanson
per T.G.T.
Title ERNEST A. HANSON, Deputy Supervisor
GEOLOGICAL SURVEY

By T.G.T.
Title District Supt.

Address Roswell, New Mexico.

Address P.O. Box CC Hobbs N.M.

NOTE.—Reports on this form to be submitted in triplicate to the Supervisor for approval.

RECEIVED

MAR 12 1973

OIL CONSERVATION COMMISSION