

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYU. S. Land Office
Las Cruces
Serial Number 032573
Lease or Permit Permit

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT RECORD OF SHOOTING.....
NOTICE OF INTENTION TO CHANGE PLANS.....	RECORD OF PERFORATING CASING.....
NOTICE OF DATE FOR TEST OF WATER SHUT-OFF.....	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING.....
REPORT ON RESULT OF TEST OF WATER SHUT-OFF.....	NOTICE OF INTENTION TO ABANDON WELL..... X
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO SHOOT.....	SUPPLEMENTARY WELL HISTORY.....

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

E.M. ELLIOTT # 1

Hobbs N.M. 6-8-35

, 19

Following is a notice of intention to do work on land under permit described as follows:

New Mexico

Lea

S.E. New Mexico

(State or Territory)

(County or Subdivision)

(Field)

Well No. 1

SW/4 Sec. 17

22-S

37E

N.M.P.M.

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

The well is located 1980 ft. N of S line and 1980 ft. E of W line of sec. 17

The elevation of the derrick floor above sea level is 3400 ft.

DETAILS OF PLAN OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

Well Drilled to Total Depth of 4077', Sulphur water encountered from 3807 to 4075'. Well Plugged back on May 31st with 74 sacks of cemented from 4077' to 3750'. Hole Stabbed dry & did not show any Oil gas or water, Well shut in and tested for 3 days no show of gas oil or water. It is now proposed to plug & Abandon well, and the following procedure will be used in plugging. Hole filled with heavy mud to bottom of 7-5/8" casing set at 2578' and Bridge set & cement plug of 20 Sacks cement run, Hole will then be filled with mud to 1200' above the top of the salt & 7-5/8" casing knocked off at this point or higher and a cement plug of 25 sacks run in hole where 7-5/8" casing knocked off. Hole will be filled to surface with heavy mud. 10-3/4" casing set at 252' and cemented to surface will be left in hole. Cellar will be filled and ~~run~~ 4" pipe marker cement in cellar to extend 4' above the level of the ground & Location restored to its original level.

Approved June 11, 1935

Company Continental Oil Co.

Ernest A. Hanson

By H. B. Hulley

Title Ernest A. Hanson, Deputy Supervisor

Title District Supt.

GEOLOGICAL SURVEY

Address Roswell, New Mexico.

Address P.O. Box CC Hobbs N.M.

NOTE.—Reports on this form to be submitted in triplicate to the Supervisor for approval.

GOVERNMENT PRINTING OFFICE 6-7083

RECEIVED

MAY 13 1973

OIL CONSERVATION COM.