		Supersedes Old
DISTRIBUTION		C-102 and C-103
SANTA FE	NI TO OIL CONSERVATION COM	AISSION Effective 1-1-65
FILE		5a. Indicate Type of Lease
U.S.G.S.		State X Fee
LAND OFFICE		5. State Cil & Gas Lease No.
OPERATOR		B-934
(DO NOT USE THIS FORM FOR PU	RY NOTICES AND REPORTS ON WELLS ROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT ATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)	RESERVOIR.
1.	· · · · · · · · · · · · · · · · · · ·	7. Unit Agreement Name
OIL CAS WELL	OTHER	
2. Name of Operator		8. Form or Lease Name State P "A"
Amerada Hess Corpo	ration	
3. Address of Operator		9. Well No.
Drawer D, Monument	, NM 88265	, 2
4. Location of Well		10. Field and Pool, or Wildcat
	FEET FROM THE West LINE AND 660	- FEET FROM Arrowhead
UNIT LETTER <u>N 1980</u>	FEET FROM THE LINE AND	
South	TION 18 TOWNSHIP 22 S RANGE 37	Е ммрм. ())))))))))))))))))))))))))))))))))))
THE JUULI LINE, SEC	TION TOWNSHIP RANGE	
mmmmmm	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	3432' GR	Lea
	Appropriate Box To Indicate Nature of Notic	Report of Other Data
		SUBSEQUENT REPORT OF:
. NOTICE OF	INTENTION TO:	
·	BUIG AND ABANDON X REMEDIAL WORK	ALTERING CASING
PERFORM REMEDIAL WORK		
TEMPORARILY ABANDON	COMMENCE DRILL	
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND	
	OTHER	
OTHER	L.J	

17. Describe Froposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903.

June and July 1977

Ran 3-7/8" bit on 2-3/8" tbg. Checked top of fill at 315' washed and circulated and drilled to 364'. Recovered red bed. Hole caving in. Mudded up and drilled and washed to 368' w/3¹/₂" EUE tbg.and 6-5/8" cut-lip shoe. Ran notched $1\frac{1}{2}$ " tbg.cplg.on $1\frac{1}{2}$ " EUE tbg, inside $3\frac{1}{2}$ " tbg and drilled and washed inside of $5\frac{1}{2}$ " csg. to 680' and outside of $5\frac{1}{2}$ " csg. to 801', stacked out $1\frac{1}{2}$ " tbg.and pulled $3\frac{1}{2}$ " tbg. Ran turned down jt.of 7" csg.as washover shoe on $5\frac{1}{2}$ " 14# csg.and circulated and washed over top of $5\frac{1}{2}$ " csg.to 388". Hung off $5\frac{1}{2}$ " csg.and pulled $1\frac{1}{2}$ " tbg. Ran 4-3/4" bit on 2-3/8" tbg.and hit metal at 389'. Pulled tbg.and bit. ' Ran mule shoe jt.2-3/8" tbg.and washed to 472'. Pulled tbg.and ran 4-3/4" bit and 4-3-1/8" DC's on 2-3/8" tbg.and circulated, drilled and washed to 621'. Ran McCullough collar locator which indicated csg. fr. 350' to 392', no csg. fr. 392' to 448', possible junk fr. 448' to452', no indication of pipe fr. 452' to 476'. Ran skirted 4-3/4" bit, 4-3-1/8" DC's on 2-3/8" tbg. and drilled to 906'. Pulled and laid down 2-3/8" tbg. Ran $1\frac{1}{2}$ " tbg.to 906' and pumped 45 sks of class C cement mixed w/2% CaCl. Pulled $1\frac{1}{2}$ " tbg. up, WOC and found no cement fill. Pumped 50 sks class C cement mixed w/2% CaCl, pulled $1\frac{1}{2}$ " tbg.up, WOC and checked top of cement at 461'. Pulled and laid down $1\frac{1}{2}$ " tbg. Pumped 425 sks class C cement down $5\frac{1}{2}$ " csg. to 388' with circulation out 7-5/8" csg. Installed P&A marker. Procedures witnessed & approved by Mr. M. Crossland, Completed 7-29-77 is true and complete to the best of my knowledge and belief.

SIGNED EBhokes	TITLE Supv. Admin. Serv.	DATE <u>8-2-77</u>
APPROVED BY Eddie W Serry	OIL & GAS INSPECTOR	NOV 21 1979
CONDITIONS OF APPROVAL, IF ANY:		

Full for the 197**7** OIL CONSERVATION COMM. HOBBS, N. M.

,	٥	2	
NO. OF COPIES RECEIVED		ž	Form C-103
DISTRIBUTION	7		Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATI	ON COMMISSION	C-102 and C-103 Effective 1-1-65
FILE	1		
U.S.G.S.	-		5a. Indicate Type of Lease
LAND OFFICE			State XX Fee
OPERATOR			5. State Oil & Gas Lease No.
DO NOT USE THIS FOR FOR POR USE TAPPLIC	DRY NOTICES AND REPORTS ON WELLS) D(FFERENT RESERVOIR, Als.)	
1. OIL CAS WELL WELL CAS	OTHER-		7. Unit Agreement Name
2. Name of Operator		······································	8. Farm or Lease Name
Amerada Hess Cor	poration		State PA
3. Address of Operator	· · · · · · · · · · · · · · · · · · ·		9. Well No.
Drawer "D" - Monu	ument, New Mexico 88265		2
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER N	1980 FEET FROM THE West LINE	AND 660 FEET FROM	Arrowhead
THE South LINE, SEC	TION 18 TOWNSHIP 228 RA	NNGE 37E NMPM.	
	15. Elevation (Show whether DF, RT,	GR, etc.)	12. County
			Lea ())))))
16. Check	Appropriate Box To Indicate Nature of	of Notice, Report or Ot	her Data
	INTENTION TO:		T REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	AL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMME	NCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING	TEST AND CEMENT JOB	
	тито	ER	
OTHER	[]		
17 Describe Proposed of Completed	Operations (Clearly state all pertinent details and	vine pertinent dates includi-	estimated data of stating any monored

ertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Clean out hole. Plug lower casing with cement. Spot cement plug at surface casing shoe and at surface casing top. Fill casing voids with brine mud. Clean location and abandon well.

Casing has parted and attempts to enter were unsuccessful because of formation cave-in and misalignment of lower section.

Expires 7/6/17

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	H.O. Porter	

Admin.Serv.Supv.

DATE July 2, 1976

DATE

Orig. Signed a	Ŋ
John Runya	4
Geologiet	

TITLE

TITLE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY