

LC-034548

Ruby Crosby

2

Arrowhead

Sec. 18, T-22-S, R-37

Lea

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug hole to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)BUR. OF LAND MGMT
ROSWELL DISTRICT1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Sun Exploration & Production Co.

3. ADDRESS OF OPERATOR

P.O. Box 1861, Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

Unit Ltr "B"

660' FNL & 2310' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3428'

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. MIRU WO rig. Install BOP.

2. Cut off tbg at 3560'. RIH w/ CIBP on WL and set at 3550'. Dump 5sx cmt on top.

3. RIH w/ 2-3/8" WS. Load hole w/ mud laden fluid. Spot 100' cmt plug 2540-2440' and (spot 100' plug 1050-950'. MUH and spot 100' plug 353-253'.)*

4. Spot cmt plug from 50' to surface. Cut off 5 1/2" and 8-5/8" csg 4' below GL. Weld on steel plate. Set permanent dry hole marker. Clean location.

APPROVED

W. CHESTER

JAN 31 1984

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Sr. Acctg. Assist.

DATE 12/30/83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

* Plugs at 1050'-950' and 353'-253' are to be in 5 1/2" casing and in annulus of 5 1/2" casing and hole also. Tag these plugs.
F. W. C.

*See Instructions on Reverse Side