AJTROVED BY --

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION P.O. Box 2088

Santa Fe, New Mexico	87504-2088
----------------------	------------

WE	ELL API NO.		
	30-025-10361		
5.	Indicate Type of Lease STATE	X FEE	
6.	State Oil & Gas Lease No. B-934		
11		7////////	7///

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: OIL. WELL X WELL OTHER 2. Name of Operator Dawson Operating Company 3. Address of Operator P. O. Box 403, Midland, Texas 79702 4. Well Location Unit Letter J : 1980 Feet From The South Line and 1980 Section 19 Township 22S Range 37E NMPM 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3416 GL, 3427.5 KB Check Appropriate Box to Indicate Nature of Notice, Report	Lea County , or Other Data DUENT REPORT OF: ALTERING CASING DIEST PLUG AND ABANDONMENT JOB
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: OIL.	W Mexico "M" State Vell No. 11 11 11 11 11 11 11 11 11
Office Of	11 col name or Wildcat almat T-Y-7R Feet From The East Line Lea County Or Other Data OUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT JOB
2. Name of Operator Dawson Operating Company 3. Address of Operator P. O. Box 403, Midland, Texas 79702 4. Well Location Unit Letter J : 1980 Feet From The South Line and 1980 Section Section Section Section Section Section Section South Section Secti	11 col name or Wildcat almat T-Y-7R Feet From The East Line Lea County Or Other Data OUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT JOB
3. Address of Operator P. O. Box 403, Midland, Texas 79702 4. Well Location Unit Letter J: 1980 Feet From The South Line and 1980 Section 19 Township 22S Range 37E NMPM 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3416' GL, 3427.5 KB 11. Check Appropriate Box to Indicate Nature of Notice, Report NOTICE OF INTENTION TO: SUBSECT PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPN PULL OR ALTER CASING CASING TEST AND CEMENT OTHER: DTHER: Plug Back 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including escentially See RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', Casing 2750-61', 2750-70', 2818-28', Casing 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE Acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE Acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE Acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE Acid, Swabbed Set CIBP @ 3045'. Perforated Yates 2706-2961', W/3250 gal 15% NEFE Acid, Swabbed Se	Feet From The East Line Lea County Or Other Data PUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT JOB
4. Well Location Unit Letter J: 1980 Feet From The South Line and 1980 Section 19 Township 22S Range 37E NMPM 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3416' GL, 3427.5 KB 11. Check Appropriate Box to Indicate Nature of Notice, Report NOTICE OF INTENTION TO: SUBSECT PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPN PULL OR ALTER CASING CASING CASING TEST AND CEMENT OTHER: Plug Back 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including escentially See RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', Casing 2750-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% NEFE acid.	Lea County Or Other Data PUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT JOB
Section 19 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3416' GL, 3427.5 KB 11. Check Appropriate Box to Indicate Nature of Notice, Report NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPN CASING TEST AND CEMENT OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including est work) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', C 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	, or Other Data PUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT JOB
PERFORM REMEDIAL WORK PLUG AND ABANDON COMMENCE DRILLING OPN PULL OR ALTER CASING CASING TEST AND CEMENT OTHER: Plug Back 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including eswork) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	ALTERING CASING PLUG AND ABANDONMENT JOB
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPN CASING TEST AND CEMENT OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including es work) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	PLUG AND ABANDONMENT
CASING TEST AND CEMENT OTHER: OTHER: Plug Back 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including es work) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	JOB
OTHER: Plug Back 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including es work) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', c 2850-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	[-
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including eswork) SEE RULE 1103. Work performed 5/15/93 to 6/3/93. Set CIBP @ 3450'. Run CBL-GR-Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	X
Perforated Seven Rivers 3123-35', 3208-20', 3237-51', 3270-84' & (138 JS). Acidized 3123-3306' w/2500 gal 15% NEFE acid, swabbed Set CIBP @ 3045'. Perforated Yates 2706-26', 2750-70', 2818-28', 2950-61' 2 JSPE (190 JS). Acidized 2706-2961' w/3250 gal 15% N	imated date of starting any proposed
Bail 167' frac sand to 3045'. Place on pump to recover load water	78 BW & swabbed dry. 2851-67', 2930-45' EFE acid. Fracced ning 92,000# 16/30 sd.
NOTE: Well originally permitted as a gas well. Revised C-102 at	tached.
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	7.00.00
SIONATURE Vice President	7-23-93
TYPE OR PRINT NAME JOE R. Dawson	DATE 7-23-93 TELEPINONE NO.915-699-144

Geologist