

# DUPLICATE

(FORM C-102)  
(REVISED 6-56)

## NEW MEXICO OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO

HOBBS OFFICE OCC

### MISCELLANEOUS NOTICES

1960 SEP 28 PM 1:20

SUBMIT THIS NOTICE IN TRIPLICATE TO THE DISTRICT OFFICE, OIL CONSERVATION COMMISSION, BEFORE THE WORK SPECIFIED IS TO BEGIN. A COPY WILL BE RETURNED TO THE SENDER ON WHICH WILL BE GIVEN THE APPROVAL, WITH ANY MODIFICATIONS CONSIDERED ADVISABLE, OR THE REJECTION BY THE COMMISSION OR AGENT, OF THE PLAN SUBMITTED. THE PLAN AS APPROVED SHOULD BE FOLLOWED, AND WORK SHOULD NOT BEGIN UNTIL APPROVAL IS OBTAINED. SEE ADDITIONAL INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION.

INDICATE NATURE OF NOTICE BY CHECKING BELOW

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	X
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (NITRO)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) Sand-Oil Frac	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Hobbs, New Mexico  
(PLACE)

September 28, 1960  
(DATE)

GENTLEMEN:

FOLLOWING IS A NOTICE OF INTENTION TO LOCATE AND WORK AS DESCRIBED BELOW AT THE

Humble Oil & Refining Company N. M. State of New Mexico WELL NO. 11 IN J  
(COMPANY OR OPERATOR) (UNIT)  
N. 1/4 SE 1/4 OF SEC. 19, T. 22S, R. 37E, NMPM, Eumont POOL  
(40-ACRE SUBDIVISION)  
Lea COUNTY.

### FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Squeeze cement all perforations.
2. Drill out cement to bridge plug at 3656', drill new hole to 3698'.
3. Run 3-inch tubing with frac packer. Set packer at 3675'.
4. Frac zone below casing seat with 10,000 gallons Humble Frac, 1-1/2# sand per gallon.
5. Pull frac tubing, run 2-inch tubing and packer and test.
6. If test unsatisfactory, perforate casing 3660-3670 feet. Set retrievable bridge plug at 3675 feet, frac interval 3660-3670 feet with 10,000 gallons Humble Frac, 1-1/2# sand per gallon.
7. Pull retrievable bridge plug and place both zones on production.

APPROVED  
EXCEPT AS FOLLOWS:

Humble Oil & Refining Company

COMPANY OR OPERATOR  
ORIGINAL  
SIGNED ARVIN D. EADY

Agent

SEND COMMUNICATIONS REGARDING WELL TO:

Humble Oil & Refining Company

Box 2347 Hobbs, New Mexico

APPROVED  
OIL CONSERVATION COMMISSION

BY [Signature]  
Engineer District 1