

**SANTA FE, NEW MEXICO**

WELL RECORD

11/11/73 12 AM 7:33

MAIL TO DISTRICT OFFICE, OIL CONSERVATION COMMISSION, TO WHICH FORM C-101 WAS SENT NOT LATER THAN TWENTY DAYS AFTER COMPLETION OF WELL. FOLLOW INSTRUCTIONS IN RULES AND REGULATIONS OF THE COMMISSION. SUBMIT IN QUINTUPPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Humble Oil & Refining Company

New Mexico State M

(COMPANY OR CREATOR)

(LEASE)

WELL NO. 24, IN SW 1/4 OF SE 1/4, OF SEC. 19, T. 22-S, R. 37-E, N14PM.

Langlie Mattix

pool.

Lea

COUNTY.

WELL IS 660 FEET FROM South LINE AND 1980 FEET FROM East LINE

OF SECTION 19 IF STATE LAND THE OIL AND GAS LEASE NO. IS B-934

DRILLING COMMENCED August 28, 1960 DRILLING WAS COMPLETED October 21, 1960

NAME OF DRILLING CONTRACTOR Lyatherwood Drilling Co.

ADDRESS Jacksboro, Texas

ELEVATION ABOVE SEA LEVEL AT TOP OF TUDING HEAD 3423 DF THE INFORMATION GIVEN IS TO BE

KEPT CONFIDENTIAL UNTIL \_\_\_\_\_, 19\_\_\_\_

## OIL SANDS OR ZONES

NO. 1, FROM 3704 TO 3746 NO. 4, FROM \_\_\_\_\_ TO \_\_\_\_\_

NO. 2, FROM \_\_\_\_\_ TO \_\_\_\_\_ NO. 5, FROM \_\_\_\_\_ TO \_\_\_\_\_

NO. 3, FROM \_\_\_\_\_ TO \_\_\_\_\_ NO. 6, FROM \_\_\_\_\_ TO \_\_\_\_\_

## IMPORTANT WATER SANDS

INCLUDE DATA ON RATE OF WATER INFLOW AND ELEVATION TO WHICH WATER ROSE IN HOLE.

NO. 1, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET. \_\_\_\_\_

NO. 2, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET.

NO. 3, FROM \_\_\_\_\_ TO \_\_\_\_\_ 1967.

NO. 4, FROM \_\_\_\_\_ TO \_\_\_\_\_ FEET.

## CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
9 5/8	32.3	new	1206	Howco Guide			Surface
2 7/8	6.5	new	3809	Howco Guide		3704-3726 & 3742-3746	Production

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2	9 5/8	1216	600	Pmp & Plug		
6 3/4	2 7/8	3820	325	Pmp & Plug		

## RECORD OF PRODUCTION AND STIMULATION

(RECORD THE PROCESS USED, NO. OF QTS. OR GALS. USED, INTERVAL TREATED OR SHOT.)

Freead perfs 3701-3726 & 3742-3746 w/15,000 gals refined oil & 30,000# sand.

Flushed w/52 bbls lss oil & breakdown w/500 gals reg acid.

**RESULT OF PRODUCTION STIMULATION** Swabbed & well flowed.

**DEPTH CLEANED OUT.**