

RECORD OF DRILL-STEM AND SPECIAL TESTS
IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3863 FEET, AND FROM 0 FEET TO 0 FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM 0 FEET TO 0 FEET.

PRODUCTION

PUT TO PRODUCING April 18, 1961

1961 MAY 31 AM 5:49

OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 28 BARRELS OF LIQUID OF WHICH 97.6 %
WAS OIL, % WAS EMULSION, 2.4 % WATER, AND % WAS
SEDIMENT. A.P.I. GRAVITY 35.0°

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

T. ANHY	T. DEVONIAN	T. OJO ALAMO
T. SALT	T. SILURIAN	T. KIRTLAND-FRUITLAND
B. XXX Rustler 1264	T. MONTOYA	T. FARMINGTON
T. YATES 2834	T. SIMPSON	T. PICTURED CLIFFS
T. 7 RIVERS 2978	T. McKEE	T. MENESEE
T. QUEEN 3588	T. ELLENBURGER	T. POINT LOOKOUT
T. SPAYBORN Penrose 3720	T. GR. WASH	T. MANCOS
T. SAN ANDRES	T. GRANITE	T. DAKOTA
T. GLORIETA	T.	T. MORRISON
T. DRINKARD	T.	T. PENN
T. TUBBS	T.	T.
T. ABO	T.	T.
T. PENN	T.	T.
T. MISS	T.	T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	200	200	Sand Gravel				
200	1245	1045	Red Bed				
1245	1345	100	Anhydrite				
1345	2780	1435	Anhydrite and Salt				
2780	3605	825	Anhydrite and Gyp.				
3605	3734	129	Anhydrite and Dolomite				
3734	3863	129	Dolomite				
	TD						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HEREWITH IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

May 27, 1961

(DATE)

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico

NAME POSITION OR TITLE Agent