

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

Form G-101
Revised (12/1/55)

NOTICE OF INTENTION TO DRILL

Notice must be given to the District Office of the Oil Conservation Commission and approval obtained before drilling or recompletion begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in QUINTUPLICATE. One copy will be retained following approval. See additional instructions in Rules and Regulations of the Commission. If State Land submit 6 Copies Attach Form G-128 in triplicate to first 3 copies of form G-101

Hobbs, New Mexico

July 21, 1961

(Place)

(Date)

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Gentlemen:

You are hereby notified that it is our intention to commence the Drilling of a well to be known as

Skelly Oil Company

(Company or Operator)

Hobbs "M"

(Lease)

Well No. 1

"1"

(Unit)

The well is

located 1650 feet from the South line and 330 feet from the West

(GIVE LOCATION FROM SECTION LINE) line of Section 20, T. 22-S, R. 37-E, NMPM. Lea County

If State Land the Oil and Gas Lease is No. B-1328

If patented land the owner is

Address

We propose to drill well with drilling equipment as follows: To be drilled with rotary tools from surface to total depth.

The status of plugging bond is Blanket Bond No. 1253688 for \$100,000.00 with Federal Insurance Company

Drilling Contractor Gackle Drilling Company, Inc.

P. O. Box 2076

Hobbs, New Mexico

We intend to complete this well in the Penrose of the Queen

formation at an approximate depth of 3700' feet.

CASING PROGRAM

We propose to use the following strings of Casing and to cement them as indicated:

Size of Hole	Size of Casing	Weight per Foot	New or Second Hand	Depth	Sacks Cement
11"	8-5/8"	24#	New	300'	300
7-7/8"	4-1/2"	10.5#	New	3700'	200

If changes in the above plans become advisable we will notify you immediately.

ADDITIONAL INFORMATION (If recompletion give full details of proposed plan of work.)

The pump & plug process will be used in cementing both strings of casing and cement will be circulated to surface behind the 8-5/8" OD casing.

Approved, 19.....
Except as follows:

* Cement must tie back
into casing

OIL CONSERVATION COMMISSION

By

Sincerely yours,

Skelly Oil Company

(Company or Operator)

By

Position

Send Communications regarding well to

Name Skelly Oil Company

Address Box 38 - Hobbs, New Mexico