

NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on setting pumping equipment and results	

Hobbs, New Mexico. 11/26/40. Place Date

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Tide Water Associated Oil Company. Anna Walden Well No. **1** in the

Company or Operator **SE of NE 1/4** of Sec. **21**, T. **22**, R. **37**, N. M. P. M.,
Penrose Area Field, **Lea** County

The dates of this work were as follows: **Beginning October 8th, 1940.**

Notice of intention to do the work was (was not) submitted on Form C-102 on _____ 19_____
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Production on this well had been going down for some time, the last few days before the pumping equipment was installed it was not flowing any oil. We installed a Happy Reduction Twin Crank Pumping Unit, and a 10-HP Fairbanks Morse Engine. We discarded the Bryan Flow Valves, steamed out the tubing to remove all paraffin, installing 5/8" x 25' Bethlehem Sucker Rods, Axelson Sure Seal Stationary Pump. The first 24-hours after the above equipment was installed well pumped approximately 20-bbls, and then dropped to about 16-bbls per day and is still holding at this figure.

Witnessed by **E.L. Layman** **Tide Water Associated Oil Company.** **Foreman**
Name Company Title

Subscribed and sworn to before me this
26 day of **November**, 19 **40**

[Signature]
Notary Public

My Commission expires **November 22, 1941**

I hereby swear or affirm that the information given above is true and correct.

Name **E.L. Layman**

Position **Foreman**

Representing **Tide Water Assoc Oil Company**
Company or Operator

Address **Drawer KK, Hobbs, New Mexico**

Remarks:

[Signature]
Name
OIL & GAS INSPECTOR
Title

