

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) sand oil frac	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO**Hobbs, New Mexico**
(Place)**March 14, 1963**
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation **E. Wood** Well No. **7** in **A**
(Company or Operator) (Unit)
NE 1/4 NE 1/4 of Sec. 22, T. 22S, R. 37E, NMPM, Tubb Gas and Drinkard Oil Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Kill well with No-Bloek mud. Pull 2-3/8" OD tubing. Set permanent plug in Baker Model "D" packer at 6373' and abandon the Drinkard Oil zone. Run correlation log. Perforate 5-1/2" OD casing, subject to logs, in Tubb zone from 5885' to 5900', 6100' to 6110', 6125' to 6133' and 6143' to 6150' with 1 crack jet shot per foot. Run 3-1/2" OD tubing with packer and retrievable bridge plug. Set bridge plug at approx. 6200' and acidize perms. from 6125' to 6133' and 6143' to 6150' with 1000 gals. 15% H.E. acid. Pull and reset bridge plug at approx. 5920' and acidize perms. from 5885' to 5900' with 500 gals. 15% H.E. acid. Reset bridge plug at approx. 6200'. Pull packer above Tubb zone and sand oil frac all perforations with 20,000 gals. refined oil and 40,000 20-40 sand with 1/40th. lb. Adomite per gal. and with ball sealers. Swab test. Pull 3-1/2" OD tubing and bridge plug. Run 2-3/8" OD tubing and packer. Recomplete well from a dual gas-oil well to a single completion in the Tubb gas zone.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....**Amerada Petroleum Corporation**

Company or Operator

By.....

Position..... **District Superintendent**
Send Communications regarding well to:Name..... **Amerada Petroleum Corporation**Address..... **Box 668 - Hobbs, New Mexico**

1. *Chrysomelidae* (100%)

[illegible]