

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

FEB 9 1948

RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

February 3, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation

Eugene Wood

Well No. 7

in the _____

Company or Operator

Lease

NE $\frac{1}{4}$ NE $\frac{1}{4}$

of Sec. 22

T. 22S

R. 37E

N. M. P. M.,

Drinkard

Field,

Lea

County.

The dates of this work were as follows:

February 3, 1948

Notice of intention to do the work was ~~(crossed out)~~ submitted on Form C-102 on February 2, 1948and approval of the proposed plan was ~~(crossed out)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6440' Total Depth, Lime. Ran Schlumberger Survey. Ran a total of 156 joints of 5 $\frac{1}{2}$ " OD, 15.5# & 17#, J-55, R-243, 8-RT, Sals Casing New and set at 6440' with 35 jts. of 17# on bottom, 10 jts. of 15.5# in middle and 111 jts. of 17# on top. Five Larkin Centralizers set at 6305', 6335', 6365', 6395', 6425'. Cemented with 450 sacks of Lone Star Regular Bulk Cement and 50 sacks of Incor Cement and plug pumped to 6352' at 11:30AM, 2-3-48. Final pressure 1600#.

Witnessed by <u>D. W. Gordon</u>	<u>Amerada Petroleum Corporation</u>	<u>Farm Boss</u>
Name	Company	Title
Subscribed and sworn before me this <u>3rd.</u>	I hereby swear or affirm that the information given above is true and correct.	
day of <u>February</u> , 19 <u>48</u>	Name <u>Roy L. S. Pitt</u>	
<u>[Signature]</u>	Position <u>Asst. Dist. Supt.</u>	
Notary Public	Representing <u>Amerada Petroleum Corporation</u>	
	Company or Operator	
My commission expires <u>May 9, 1949</u>	Address <u>Drawer D, Monument, New Mexico</u>	

Remarks:

APPROVED

FEB 9 1948

OIL & GAS INSPECTOR

Title

Handwritten text, possibly a signature or date, located at the bottom left of the page.