

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

JAN 16 1948

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

g January 11, 1948 Monument, New Mexico  
Date Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation Eugene Wood Well No. 7 in the  
Company or Operator Lease  
NE 1/4 NE 1/4 of Sec. 22, T. 22S, R. 37E, N. M. P. M.,  
Drinkard Field, Lea County.

The dates of this work were as follows: January 11, 1948

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on January 11, 19 48  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2766' Total Depth, Lime. Ran 45 joints of 8-5/8" OD, 20#, H-40, R-3, 8-RT, SS Casing New with 25 jts. on bottom and 20 jts. on top and ran 49 joints of 8-5/8" OD, 32#, R-1, 8-V-Thd., Lap Weld Casing Second Hand in the middle for a total of 94 jts. and set at 2758'. Cemented with 1500 sacks of Dewey Reg. Bulk Cement (first 1000 sacks mixed 3% Howoogel) and 50 sacks of Incor Cement and plug pumped to 2674' at 6:45 PM, 1-11-48. Final pressure 1100#. Cement started circulating when plug reached 1200'.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Farm Boss  
Name Company Title

Subscribed and sworn before me this \_\_\_\_\_

I hereby swear or affirm that the information given above is true and correct.

11th. day of January, 19 48

Name Don Tapp

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires My Commission Expires May 9, 1948

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date Jan 16 1948

Ray Yahruegh  
Name  
OIL & GAS INSPECTOR  
Title