

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

JUN 21 1948

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Setting Casing	X

June 19, 1948,

Date

Monument, New Mexico.

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation E. Wood Well No. 8 in the
Company or Operator Lease
W. W. W. of Sec. 22, T. 22S, R. 37E, N. M. P. M.,
Drinkard Field, Lea County.

The dates of this work were as follows: June 18, 1948.

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on June 18, 19 48
and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

6455' Total Depth Lime, Ran 209 Joints of 5½" OD 15.5#, J-55, R-2, 8 RT, Spang Seamless steel Casing New, and set at 6432' and cemented with 400 sacks 4% Howcogel and 200 sacks Atlas Common cement for a total of 600 sacks and plug pumped to 6373' @ 11:10PM June 18, 1948 with a maximum pressure of 1500#, Ran 5 Baker centralizers set at 6417-6387-6357-6327 and 6297, also 10 Weatherford Scratchers set at 6410-6403-6396-6389-6382-6375-6368-6361-6354-6347.

Ran Schlumber Survey before running casing and their bottom checked 6450'. We made no corrections in total depth.

Witnessed by D. F. Furse Amerada Pet. Corp. Foreman
Name Company Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

19 day of June 19 48

Name Don Tipp

Willis Hilde Taylor
Notary Public

Position Asst. Dist. Supt.

Representing Amerada Pet. Corp.
Company or Operator

My commission expires _____

Address Drawer D, Monument, New Mexico.

Remarks:

APPROVED

Date JUN 21 1948

Roy Yarbrough
Name
Inspector
Title

[illegible]