

# OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED  
SEP 22 1948  
FIELD OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plugging Back	X

September 20, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation E. Wood Well No. 9 in the \_\_\_\_\_  
Company or Operator Lease  
S 1/2 NE 1/4 of Sec. 22, T. 22S, R. 37E, N. M. P. M.,  
Brunson Field, Lea County.

The dates of this work were as follows: September 16-20, 1948

Notice of intention to do the work was ~~(submitted)~~ submitted on Form C-102 on September 16, 1948  
and approval of the proposed plan was ~~(submitted)~~ obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

**6441' Plugged Back Depth.** Drilled out old plastic 6445' - 6450' and plugged back with 20 gallons Dowell Plastic to 6441'. Maximum pressure 2000#. Ran 2-3/8" OD, EUE, Tubing and set Guiberson Hookwall Packer at 6362', bottom of tubing at 6433'. Started swabbing and in 24 hrs. to 6AM, 9-19-48, swabbed 126.27 bbls. fluid, 3.8% water, 200' of fluid in hole. Stopped swabbing and perforated 5 1/2" casing with Lane Wells 6403'-16', 60 shots. Ran tubing and set packer at 6361'. In 9 hrs. to 6AM, 9-20-48, swabbed 67.38 bbls. fluid, 1.6% water, fair gas, 300'-350' of fluid in hole.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Farm Boss  
Name Company Title  
Subscribed and sworn before me this \_\_\_\_\_  
20th. day of September 1948  
Willie Hain Taylor  
Notary Public  
I hereby swear or affirm that the information given above is true and correct.  
Name E. Wood  
Position Asst. Dist. Supt.  
Representing Amerada Petroleum Corporation  
Company or Operator  
My commission expires \_\_\_\_\_ Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date SEP 22 1948

Roy Yashinski  
Name  
OIL & GAS INSPECTOR  
Title

Handwritten signature