


## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Squeezing and Plugging Back	X

September 10, 1948

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation E. Wood Well No. 9 in the \_\_\_\_\_  
Company or Operator Lease  
SW 1 NE 1 of Sec. 22, T. 22S, R. 37E, N. M. P. M.,  
Brunson Field, Lea County.

The dates of this work were as follows: September 7-10, 1948

Notice of intention to do the work was (~~received~~) submitted on Form C-102 on September 7, 1948  
and approval of the proposed plan was (~~received~~) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

8025' Total Depth, Granite, 6482' Plugged Back Depth. Set Baker Model K Cement Retainer at 7850' and broke formation with 3 bbls. water with 1200#. Mixed 56 sx common cement and pumped 30 sx below retainer with 2000# pressure. Pulled up to 7800' and reversed out 20 sx. Pulled up and spotted 25 sx common cement from 6550' to 6350' and reversed out approximately 1 sack cement at 6350' at 10:30PM, 9-7-48. Drilled out cement 6350' to 6482' and ran Lane Wells Gamma Ray Survey. Perforated 5 1/2" casing 6418' - 6445' with 108 shots. Ran Guiberson Hookwall Packer and 208 jts. 2-3/8" OD, EUE Tbg, displaced mud with 150 bbls. oil and set packer at 6343', tbg. at 6474'. Started swabbing and in 8 1/2 hrs. to 6:00AM, 9-10-48 swabbed 26.22 bbls. oil, 2% drilling mud. Tubing load is 28.11 bbls. Have little vacuum.

Witnessed by D. Gordon Name Amerada Pet. Corp. Company Farm Boss Title \_\_\_\_\_

Subscribed and sworn before me this 10th. day of September 19 48

Will Hails Taylor

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name W. T. Tapp

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires \_\_\_\_\_

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

SEP 13 1948

W. T. Tapp  
Name  
OIL & GAS INSPECTOR  
Title

*[Faint, illegible text covering the majority of the page, appearing to be bleed-through from the reverse side.]*

*[Handwritten signature or initials.]*

*[Handwritten text, possibly a date or reference number, written diagonally in the bottom left corner.]*